

LED BULB E27

LED BULB E27



LED BULB E27



TIS.1955-1951
TIS.2780-2562

*Signature
Designed by WIP*

LED BULB E27

Specification

The light shell is thicker than E27 standard base lamp, provide a long life time usage and better heat transfers. Latest LED design technology from Lumileds which can provides high efficiency 100lm/W, input voltage range 100-265 VAC. The constant current driver design provides an output that is regulated to deliver a constant current. This is a perfect option for energy saving consumption and commercial lighting applications with an aesthetic streamline design. Idea for home lighting, office, hotel, vessel, solar system, etc.

Base Type	E27	CCT	- Warm White
Work Temperature	-10°C to + 65°C		- Cool Daylight
LED Light Source	Lumileds	Driver	- Daylight
LED Life Time	20,000 hrs.		Constant Current
CRI	>80	Warranty	1 Years



Model	Power (W)	Input (V)	Lumen Flux (lm)	Efficiency (lm/W)	Wattage Equalvalent	Housing	Standard
E27 3W	3	230±10	270	90	30	A50	
E27 5W	5	100-250	500	100	50	A60	
E27 7W	7	100-250	700	100	70	A60	
E27 9W	9	100-250	900	100	90	A60	
E27 11W	11	100-250	1,100	100	110	A60	
E27 13W	13	100-250	1,300	100	130	A60	

International Electrotechnical Commission - IEC

IEC 61000-4-5 : Surge Protection



Products of Thailand

LED BULB E27



TIS.1955-1951
TIS.2780-2562



*Signature
Designed by WIP*

LED BULB E27 : DC TO DC CONVERTER

Specification

The light shell is E27 standard base lamp. Has convenient installation, operation, and maintenance also provide a long life-time usage. The distinction of this model is DC converter, buck range is 10-26 VDC. DC-to-DC converters can convert one DC battery voltage level which may be higher or lower, by storing the input energy temporarily and then releasing that energy to the output at a same voltage. This is a perfect option for energy saving and commercial lighting applications with an aesthetic streamline design. Suitable for home lighting, office, hotel, vessel, solar system, etc.

Base Type	E27	CCT	- Warm White
Work Temperature	-10°C to +65°C		- Cool Daylight
LED Light Source	Lumileds		- Daylight
LED Life Time	20,000 hrs.	Driver	DC Convert
CRI	>80	Warranty	1 Years

Model	Power (W)	Input (V)	Lumen Flux (lm)	Efficiency (lm/W)	Wattage Equivalent	Housing
E27 5W	5	10-26VDC	500	100	50	A60
E27 7W	7	10-26VDC	700	100	70	A60
E27 9W	9	10-26VDC	900	100	90	A60



Products of Thailand

LED BULB E27



TIS.1955-1951
TIS.2780-2562


*Signature
Designed by WIP*

LED BULB E27 : DIMMABLE

Specification

The light shell is E27 standard base lamp and modern design offers a better perspective, low power consumption and energy saving, clean and smooth. Has convenient installation, operation, and maintenance also provide a long life-time usage. Dimmable LED lights are great for creating mood lighting. The product is designed to be use with LED dimmer switch only, cannot be use with TRIAC dimmer. This is a perfect option for commercial lighting applications with an aesthetic streamline design. Suitable for home lighting, office, hotel, spa, etc.

Base Type	E27	CCT	- Warm White
Work Temperature	-10°C to + 65°C		- Cool Daylight
LED Light Source	Lumileds		- Daylight
LED Life Time	20,000 hrs.	Warranty	1 Years
CRI	>80		

Model	Power (W)	Input (V)	Lumen Flux (lm)	Efficiency (lm/W)	Wattage Equalvalent	Housing	Standard
E27 9W	9	100-265	900	100	90	A60	 TIS.1955-1951 TIS.2780-2562



Products of Thailand

TIS.1955-1951
TIS.2780-2562