

# LED BULB E27

## LED BULB E27



# LED BULB E27



TIS.1955-2551  
TIS.2780-2562



*Signature*  
Designed by WIP

## LED BULB E27


### Specification

The light shell is thicker than E27 standard base lamp, provide a long life time usage and better heat transfers. Latest LED design technology from Lumileds which can provides high efficiency 100lm/W, input voltage range 100-265 VAC. The constant current driver design provides an output that is regulated to deliver a constant current. This is a perfect option for energy saving consumption and commercial lighting applications with an aesthetic streamline design. Idea for home lighting, office, hotel, vessel, solar system, etc.

Base Type	E27
Work Temperature	-10°C to +65°C
LED Light Source	Lumileds
LED Life Time	20,000 hrs.
CRI	>80

CCT	3000K (Warm White)
	4000K (Cool White)
	6500K (Daylight)
Warranty	1 Year

### Dimension



Model	Power (W)	Input (V)	Lumen Flux (lm)	Efficiency (lm/W)	Wattage Equivalent	Housing	Standard
E27 5W	5	100-250	500	100	50	A60	
E27 7W	7	100-250	700	100	70	A60	
E27 9W	9	100-250	900	100	90	A60	
E27 11W	11	100-250	1,100	100	110	A60	
E27 13W	13	100-250	1,300	100	130	A60	

International Electrotechnical Commission - IEC

IEC 61000-4-5 : Surge Protection



Products of Thailand