## LED BULB E27



## LED BULB E27: DC TO DC CONVERTER

## Specification

The light shell is E27 standard base lamp. Has convenient installation, operation, and maintenance also provide a long life-time usage. The distinction of this model is DC converter, buck range is 10-26 VDC. DC-to-DC converters can convert one DC battery voltage level which may be higher or lower, by storing the input energy temporarily and then releasing that energy to the output at a same voltage. This is a perfect option for energy saving and commercial lighting applications with an aesthetic streamline design. Suitable for home lighting, office, hotel, vessel, solar system, etc.

9	9		•				
Base Type	E27	ССТ	3000K (Warm White)	Dimension	1		<u> </u>
Work Temperature	-10°C to +65°C		4000K (Cool White)		38 mm.	(	
LED Light Source	Everlight		6500K (Daylight)				119 mm.
LED Life Time	20,000 hrs.	Driver	DC Convert				
CRI	>80	Warranty	1 Year				

Model	Power (W)	Input (V)	Lumen Flux (lm)	Efficiency (lm/W)	Wattage Equalvalent	Housing
E27 5W	5	10-26VDC	500	100	50	A60
E27 7W	7	10-26VDC	700	100	70	A60
E27 9W	9	10-26VDC	900	100	90	A60

