LED BULB E27

LED BULB E27



LED BULB E27



LED BULB E27: DC TO DC CONVERTER

Specification

The light shell is E27 standard base lamp. Has convenient installation, operation, and maintenance also provide a long life-time usage. The distinction of this model is DC converter, buck range is 10-26 VDC. DC-to-DC converters can convert one DC battery voltage level which may be higher or lower, by storing the input energy temporarily and then releasing that energy to the output at a same voltage. This is a perfect option for energy saving and commercial lighting applications with an aesthetic streamline design. Suitable for home lighting, office, hotel, vessel, solar system, etc.

3	3						
Base Type	E27	ССТ	1800K, 2000K, 2700K,	Dimension	<u> </u>		<u> </u>
Work Temperature	e -10°C to +65°C		3000K, 3500K, 4000K,		38 mm.		
LED Light Source	Everlight		5000K, 6500K, 7000K,				119 mm.
LED Life Time	20,000 hrs.		7800K				
CRI	>80 (1800K-6500K)	Driver	DC Convert				
	>90 (2700K-7800K)	Warranty	1 Year			<u> </u>	

Model	Power (W)	Input (V)	Lumen Flux (lm)	Efficiency (lm/W)	Housing
E27 5W	5	10-26VDC	675	135	A60
E27 7W	7	10-26VDC	945	135	A60
E27 9W	9	10-26VDC	1,215	135	A60

